



## UULA LASURE

### TRANSPARENT WOOD STAIN

#### DESCRIPTION

- Semi-gloss
- Structure of the wood remains visible

UULA LASURE is a natural paint made from line oil and natural resins. The color can be obtained with earth colors (like f.ex. ochre) and white titane. UULA LASURE contains an aromatic solvent (max. 300 g/l). It's possible to dilute with turpentine.

#### TECHNICAL PROPERTIES

Colors	see color card, other colors on demand
Use	for all substrates in wood in the interior ; at the exterior only on red cedar or preserved wood
Coverage	9 - 15 m <sup>2</sup> /l for planed timber
Tools	circular or leveling paint brush
Drying time	dry after 5 to 8 hours, ready for next layer after 24 hours
Containers	0,9 l, 2,7 l, 9 l (transparent) 1 l, 3 l, 10 l (colored)

#### APPLICATION

Clean the wood and scrape the unstable parts.

Apply one, two or three layers, dependant of the desired color or transparency. Sand down the first layer in order to take off the lifting fibres. Don't sand down (or almost not) the second and the third layer.

#### REMARKS

The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In any case, we do recommend to consider the type of substrate and the climatic conditions before applying our products or to apply a test surface in order to analyse the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.