



UULA NORDIQUE

PAINT FOR WOOD, BOILED IN THE TRADITIONAL WAY

DESCRIPTION

- Matt
- High permeability to water vapour

UULA NORDIQUE is a natural paint made from line oil and natural resins. The color can be obtained with earth colors (like f.ex. ochre) and white titan. UULA LASURE contains an aromatic solvent (max. 300 g/l). It's possible to dilute with turpentine.

TECHNICAL PROPERTIES

Colors	see color card, other colors on demand
Use	for all substrates in untreated wood, in the interior and exterior
Consumption	3 - 5 m ² /l (2 - 4 m ² /l with the airless)
Tools	brush, roller or airless (nozzle : 5.15 0.0015 inches / 45 degrees)
Drying time	dry after 2 hours, ready for next layer after 24 hours
Containers	1 l, 3 l, 10 l (certain colors in 20 l)

APPLICATION

Apply two layers of nordique on a clean surface.

Dilute the first layer with 30% of water ; apply the second layer on a pure way after minimum 24 hours.

In order to obtain a good and long lasting result, it is recommended to apply a new layer after 5 years.

REMARKS

The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In any case, we do recommend to consider the type of substrate and the climatic conditions before applying our products or to apply a test surface in order to analyse the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.