



ECOCERA

EMULSION BASED ON NATURAL BEESWAX AND MARSEILLE SOAP

DESCRIPTION

ECOCERA is a natural wax to be used as a protection coat against dirt and for rendering surfaces watertight. ECOCERA is composed of very pure bleached bee wax, free of solvents, and emulsified in Marseille soap, prepared the old fashioned way.

APPLICATION AREA

ECOCERA is used as a protection layer on inner walls. It may be applied on every type of slick background (old or new) such as lime wash, silicate paint, marble finishes CORISTIL, DECORLUX, VENESTUK and others...

ECOCERA is applied to homogenize and enhance the natural shiny and velvet effect of the CORIDECOR decorative range, without altering the colour of the finish.

ECOCERA is especially suited to protect surfaces against dirt in crowded places like stairs, bars and reception areas, and also to protect surfaces against humidity, such as in kitchens and bathrooms.

TECHNICAL DATA

0,980 kg/l Specific gravity Product subcategory (directive 2004/42/EC) cat. A/I VOC limit value < 300 gr/l (< 200 gr/l from 01.01.2010) VOC maximum content < 100 gr/l Dry residue (at 105°C) 11% pH-value 6,5 - 7,0 Colour off white Consumption 30 - 40 m²/l per layer Packing paste in containers of 0,75 l, 2,5 l and 5 l Storage in suitable environment 12 months

PREPARATION OF THE BACKGROUND

The background must be stable, clean and dry.

APPLICATION

ECOCERA is a ready to use product and should only be stirred thoroughly before use. When the paste is too hard due to low temperature, warm up the product at about 30°C.

Apply the wax evenly with a soft cloth, a sponge or a brush to spread the product equally. When completely dry, polish the surface firmly with a clean dry cloth to obtain the natural shiny effect.

	ARTE CONSTRUCTO	MOLENBERGLEI 18	B-2627 SCHELL	E
TEL: +32 (0)3 880 73 73	FAX: +32 (0)3 880 73 70 WWW.ARTE		NSTRUCTO.COM	INFO@ARTECONSTRUCTO.BE





PACKING AND STORAGE

Plastic containers of 0,75 l, 2,5 l and 5 l.

The stability of the product is at least 12 months provided being stored in airtight closed containers at temperatures between $+5^{\circ}$ C and $+35^{\circ}$ C. Store in a cool and dry environment. Protect from frost, direct sunlight and heat sources.

SAFETY PRECAUTIONS

No special safety measures are required for the environment or people. Anyhow we advise to avoid prolonged contact with the skin. In case of contact with eyes, rinse immediately with plenty of clean water. If swallowed, or irritation is observed, seek medical advice immediately and show this container or label.

Keep away from children. Do not litter.

REMARKS

The current data sheet replaces any previous version.

Our advice and information are given in good faith and depending on the latest developments of our products. We guarantee the consistent quality of our products, but do not accept any liability concerning their application. In any case, we do recommend to consider the type of substrate and the climatic conditions before applying our products or to apply a test surface in order to analyse the suitability of the product for the given substrate.

In case of doubt regarding the substrate, consult our technical service department.

	ARTE CONSTRUCTO	MOLENBERGLEI 18	B-2627 SCHELLE			
TEL: +32 (0)3 880 73 73	FAX: +32 (0)3 880 73	70 WWW.ARTECO	NSTRUCTO.COM	INFO@ARTECONSTRUCTO.BE		
					-	